

# **Selectone**

## **ST-50 APPLICATION NOTE #0312**

**FOR USE WITH : MOTOROLA GM350**

**APPROVAL DATE: 21AUG97S BY: RTS**

XX

### **CONNECTION**

#### **ENCRYPTION UNIT**

#### **RADIO**

XX

(3)	(+) SUPPLY INPUT	RED	JUNCTION OF R0641 AND SW_B+	
(9)	(-) SUPPLY INPUT	BLACK	GROUND	
(11)	RX AUDIO INPUT	BLUE	JUNCTION OF R0184 AND C0181	
(1)	RX AUDIO OUTPUT	WHT/BLU	JUNCTION OF C0181 AND U0103-7	
(12)	TX AUDIO INPUT	GREEN	J0103-3	TX_AUDIO_SEND
(13)	TX AUDIO OUTPUT	WHT/GRN	J0103-1	TX_AUDIO_RET
(6)	PTT INPUT	YELLOW	J0101-4	MIC_PTT
(10)	PTT OUTPUT	BLK/YEL	J0101-4	MIC_PTT
(7)	CLEAR/CIPHER	BROWN	ADD SWITCH	
(5)	COS	BLK/ORG	JUNCTION OF R0404 AND R0405	
(8)	AMP ENABLE	BLK/BRN	N/C	
(2)	RS-232 IN	VIOLET	N/C	
(4)	RS-232 OUT	WHT/ORG	N/C	

XX

**NOTES: REMOVE R0145 AND C0181. ADD A 30K RESISTOR IN SERIES WITH THE WHT/GRN. ADD A 0.1MFD (100NF) CAPACITOR IN SERIES WITH THE WHT/BLU WIRE. PROGRAM THE ST-50 TO COMMON PTT.**

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE  
**SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376**  
**(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com**