

Selectone

ST-025B & BGP KIT APPLICATION NOTE #0348

FOR USE WITH : MOTOROLA GP350 APPROVAL DATE: 11 MAY 98R BY: CPE

CONNECTIONS

VOICE ENCRYPTION UNIT		RADIO	
(3)	(+) SUPPLY INPUT	RED	POWER SWITCH PIN 5
(9)	(-) SUPPLY INPUT	BLACK	P1-8 GND
(11)	RX AUDIO INPUT	BLUE	P1-7 RX AUDIO INPUT
(1)	RX AUDIO OUTPUT	WHT/BLU	P1-6 RX AUDIO OUTPUT
(12)	TX AUDIO INPUT	GREEN	P1-5 TX AUDIO INPUT
(13)	TX AUDIO OUTPUT	WHT/GRN	P1-4 TX AUDIO OUTPUT
(6)	PTT INPUT	YELLOW	P1-10 PTT
(7)	CLEAR/CYPHER	BROWN	P1-9 MON BUTTON
(4)	BEEP	WHT/ORG	JUNCTION OF R464 AND R465
(8)	CODE #2	BLK/BRN	P1-13 AMP ENABLE

NOTES: REMOVE R455 AND R506 IN RADIO. ADD A 24K RESISTOR IN SERIES WITH THE WHT/GREEN WIRE. ADD A 30K RESISTOR IN SERIES WITH THE WHT/BLU WIRE.

~~R4=33K R21=33K R35=33K R28=33K~~

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com