

Selectone

ST-120 APPLICATION NOTE #1209

FOR USE WITH: **G.E. MASTR II**

APPROVAL DATE: 24JUL85 BY: JFO

CONNECTIONS		
TONE UNIT		RADIO
		P908 C.G. option connector
(+) SUPPLY	(RED)	4 <---
(-) SUPPLY	(BLACK)	9 <---
TONE INPUT	(GREEN)	1 <---
MONITOR/HOOK SWITCH	(BROWN)	3 <---
DECODE LATCHED	(WHT/ORG)	5 <---
DECODE MOMENTARY	(WHT/VIO)	~~~~~ Connect as required
LAMP (-)	(BLK/ORG)	~~~~~ Connect as required
SET	(WHITE)	Normally not used

MODIFICATIONS		
TONE UNIT		RADIO
USER: None		
JU-1 at "B"		
JU-3 IN		If a normal G.E. Hookswitch is used, P908 pin 3 connects to (-) Supply to monitor.
FACTORY: None		

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com