

Selectone

ST-139 APPLICATION NOTE #1367

FOR USE WITH: MIDLAND MODEL 70-335

APPROVAL DATE: 18APR97s BY:RTS

=====

CONNECTIONS

TONE UNIT

RADIO

MONITOR	BROWN	J502-3 (Mic)
P.T.T. (ENCODE ENABLE)	YELLOW	8
DECODE (-)	WHT/ORG	14
HI PASS FILTER OUTPUT	WHT/BLU	Junction of R116 and C132
HI PASS FILTER INPUT	BLUE	Junction of R116 and C133
TONE INPUT	GREEN	3
ENCODE OUTPUT	WHT/GRN	6
(+) SUPPLY	RED	7
(-) SUPPLY	BLACK	13

NOTES:

Unless otherwise indicated, the RADIO connections called out above refer to the fourteen in-line holes normally used for tone option.

MODIFICATIONS:

TONE UNIT:
Cut JU1

RADIO:

Remove JP-5; Remove R116;
Use VR452 to set tone transmit level.

=====

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com