

Selectone

ST-139 APPLICATION NOTE #1369

FOR USE WITH: MOTOROLA MOCOM 35

APPROVAL DATE: 18APR97S BY: RTS

CONNECTIONS

TONE UNIT

RADIO

MONITOR	(BROWN)	-----< 32	<----- TO P.L. HANGUP BOX
P.T.T. (ENCODE ENABLE)	(YELLOW)	-----< 28	<----- NOTE 3
DECODE (-)	(WHT/ORG)	-----*< 13	<----- NOTE 1
HI PASS FILTER OUTPUT	(WHT/BLU)	-----< 35	<----- NOTE 2
TONE INPUT	(GREEN)	-----< 14	<----- NOTE 2
ENCODE OUTPUT	(WHT/GRN)	-----< 3	<-----
(+) SUPPLY	(RED)	-----< 17	<-----
(-) SUPPLY	(BLACK)	-----< 33	<-----

1,3,5,6,9,11, & 13 are NOT USED

MODIFICATIONS

TONE UNIT

RADIO

USER: Remove JU%

FACTORY: NONE

1. Remove the jumper between 13 and 16 and replace with the WHT/ORG wires as indicated above.

2. Remove the jumper between 14 and 35.

3. Ensure the jumper between 36 and 37 is IN.

NOTE: ST-138M35 is a kit consisting of an ST-138 & an ST-950M35 cable.

Rev. 14SEP87 JNS

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com