

Selectone

ST-139 APPLICATION NOTE #1371

FOR USE WITH: Motorola Mocom 70 Series Mobiles

APPROVAL DATE: 08MAY97S BY: RTS

CONNECTIONS

TONE UNIT

RADIO

o---	MONITOR	BROWN	-----	11
o---	P.T.T. (ENCODE ENABLE)	BLK/YEL	-----*	9
o---	HI PASS FILTER MUTE	VIOLET	-----	11
o---	HI PASS FILTER OUTPUT	WHT/BLU	----/\//\/--	3
o---	HI PASS FILTER INPUT	BLUE	-----	4
o---	TONE INPUT	GREEN	-----	1
o---	ENCODE OUTPUT	WHT/GRN	-----	10
o---	(+) SUPPLY	RED	-----	16
o---	(-) SUPPLY	BLACK	-----	11

MODIFICATIONS

TONE UNIT

RADIO

USER:

Remove jumpers JU1
SET JU2 TO B

Remove jumpers 3 to 4, 8 to 9,
and 10 to 12. Ensure jumper 6 to
7 is IN.

This application requires the use
of a "PL" hang-up box or "PL"
switch at the radio control head.

FACTORY:

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376

(800) 227-0376

• **FAX (510) 781-5454** •

E-Mail admin@selectone.com