

# Selectone

## ST-139 APPLICATION NOTE #1372

FOR USE WITH : GE EXECUTIVE II

APPROVAL DATE: 09MAY97S BY: RTS

TONE UNIT		CONNECTIONS		RADIO	
ST-956E2 Application Cable				J907	
10	P.T.T. (ENCODE ENABLE)	BLK/YEL		10	DPTT
5	HI PASSS FILTER MUTE	VIOLET		4	C.G. DISABLE
1	HI PASS FILTER OUTPUT	WHT/BLU		7	TONE REJ.FILT. OUT
11	HI PASS FILTER INPUT	BLUE		1	TONE REJ. FILT. IN
12	TONE INPUT	GREEN		8	VOL. HI
13	ENCODE OUTPUT	WHT/GRN		6	C.G. HI
3	(+) SUPPLY	RED		2	10V REG
9	(-) SUPPLY	BLACK	*	4	A-
7	MONITOR	BROWN			

2,4,6, & 8, ARE NOT used.

MODIFICATIONS		RADIO	
TONE UNIT		RADIO	
USER:		PL19D423191G1-3 (Mobile):	
JU1=OPEN		Remove the jumpers H36 toH37, H38 to H39 and H47 to H48.	
		Add a jumper from H36 to H38and from H37 to H44.	
FACTORY: Splice the BROWN wire to the BLACK wire.		Add a diode (CR919) betweenH47 & H48 (cathode to H47).	
		PL19D423307G1 (Base):	
		Remove the jumpers H1 to H2 and H11 to H12. Add a jumper from H1 to H11 and H12 to H18.	

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

**SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376**  
**(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com**