Selectone

ST-139 APPLICATION NOTE #1379

FOR USE WITH : MIDLAND 70-330 **APPROVAL DATE: 18JUL97S BY: RTS**

CONNECTION

	ENCRYPTION UNIT		RADIO
(3)	(+) SUPPLY INPUT	RED	IC401-2
(9)	(-) SUPPLY INPUT	BLACK	GROUND
(11)	HI PASS FILTER INPUT	BLUE	(-) SIDE OF C139
(1)	HI PASS FILTER OUPUT	WHT/BLU	(+) SIDE OF C139
(12)	TONE IN	GREEN	③----------C454
(13)	CTCSS TONE OUTPUT	WHT/GRN	⑥----------C325
(6)	ENCODE ENABLE	YELLOW	⑧----------D451
(10)	ENCODE ENABLE	BLK/YEL	N/C
(7)	MONITOR	BROWN	JUNCTION OF R126 AND D113
(4)	DECODE (-)	WHT/ORG	N/C
(5)	DECODE (+)	BLK/ORG	N/C
(8)	MONITOR	BLK/BRN	N/C
(2)	HI PASS FILTER MUTE	VIOLET	GROUND

NOTES: ON ST-139 REMOVE JU1. IN RADIO REMOVE C139.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 23210 BERNHARDT ST. HAYWARD, CA. 94545 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com