

Selectone

ST-139

APPLICATION NOTE #1385

FOR USE WITH: Ranger SRL-1645M

APPROVAL DATE: 02SEP97S BY: RTS

=====

CONNECTIONS

TONE UNIT

RADIO

	TONE UNIT		RADIO
7	MONITOR	BROWN	USER SUPPLIED MONITOR SW. GND=MUTE
10	P.T.T. (ENCODE ENABLE)	BLK/YEL	J201-2
4	DECODE (-)	WHT/ORG	CONNECT TO VIOLET (HPF MUTE)
1	HI PASS FILTER OUTPUT	WHT/BLU	JUNCTION C175 AND C166
2	HI PASS FILTER MUTE	VIOLET	CONNECT TO WHT/ORG (DECODE -)
12	TONE INPUT	GREEN	JUNCTION C164 AND C175
13	ENCODE OUTPUT	WHT/GRN	J201-4
3	(+) SUPPLY	RED	J201-1
9	(-) SUPPLY	BLACK	J201-7

=====

MODIFICATIONS

TONE UNIT

RADIO

USER:

REMOVE J102.

FACTORY:

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com