

Selectone

ST-139 APPLICATION NOTE #1387

FOR USE WITH: WILSON HH SERIES HANDHELD AND
REGENCY TRPH/TRPU/MCPL/MCPH/MCPU/ UTILICOM APPROVAL DATE: 16SEP97S BY: RTS

CONNECTIONS

TONE UNIT

RADIO

TONE UNIT	RADIO	TONE OPTION CONNECTOR
○ P.T.T. (ENCODE ENABLE) (YELLOW)	8	> GREY
○ MONITOR (BLK/BRN)	7	> VIOLET
○ HI PASS FILTER MUTE (VIOLET)	8	> BROWN
○ HI PASS FILTER OUTPUT (WHT/BLU)	5	> GREEN
○ TONE INPUT (GREEN)	4	> YELLOW
○ ENCODE OUTPUT (WHT/GRN)	3	> ORANGE
○ (+) SUPPLY (RED)	2	> RED
○ (-) SUPPLY (BLACK)	1	> BROWN
○ MONITOR (BRN)		

MODIFICATIONS

TONE UNIT

RADIO

USER: NONE.

Remove jumper between pins 4 and 5, generally located at the top of the radio from VOL. control to the YELLOW wire. Except in. UTILICOM remove R219

FACTORY:

In some models both sides of the Tone Squelch switch are connected to ground. In this case Tone Squelch will not activate. To remedy this cut the jumper from the switch (VIOLET WIRE) to GND.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com