

# Selectone

## ST-139 APPLICATION NOTE #1400

FOR USE WITH: E.F. Johnson Fleetcom

APPROVAL DATE: 16DEC97S BY:RTS

=====

### CONNECTIONS

TONE UNIT

RADIO

CONNECTIONS		TONE UNIT	RADIO
8	MONITOR	BLK/BRN	NOT USED
7	MONITOR	BROWN	J2-1
10	P.T.T. (ENCODE ENABLE)	BLK/YEL	NOT USED
6	P.T.T. (ENCODE ENABLE)	YELLOW	J2-11
5	DECODE (+)	BLK/ORG	NOT USED
4	DECODE (-)	WHT/ORG	BASE Q13
1	HI PASS FILTER OUTPUT	WHT/BLU	C50 (-)
11	HI PASS FILTER INPUT	BLUE	C50 (+)
12	TONE INPUT	GREEN	J2-9
13	ENCODE OUTPUT	WHT/GRN	J2-10
3	(+) SUPPLY	RED	J4-3
9	(-) SUPPLY	BLACK	J2-5

=====

### MODIFICATIONS

TONE UNIT

RADIO

MODIFICATIONS		TONE UNIT	RADIO
USER:	REMOVE JU1		REMOVE CAPACITOR C50. Be sure the jumper from J2-2 to J2-4 is installed.
FACTORY:			Be sure that the jumper from J2-5 to J2-8 is installed.

=====

ENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION.  
SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE  
SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376

**(800) 227-0376**

• **FAX (510) 781-5454** •

**E-Mail [admin@selectone.com](mailto:admin@selectone.com)**