

# Selectone

## ST-139 APPLICATION NOTE #1401

FOR USE WITH: E.F. JOHNSON TRANSCOM II & FLEETCOM II APPROVAL DATE:16DEC97S BY:RTS

### CONNECTIONS TONE UNIT

### RADIO

|                        |           | LATE MODEL  |    | EARLY MODEL |
|------------------------|-----------|-------------|----|-------------|
| MONITOR                | (BROWN)   | -----o J305 | or | J1-14 <---  |
| P.T.T. (ENCODE ENABLE) | (YELLOW)  | -----o J308 | or | J302 <---   |
| DECODE (-)             | (WHT/ORG) | -----o J209 | or | J209 <---   |
| TONE INPUT             | (GREEN)   | -----o J211 | or | J211 <---   |
| ENCODE OUTPUT          | (WHT/GRN) | -----o J310 | or | J301 <---   |
| (+) SUPPLY             | (RED)     | -----o J304 | or | J402 <---   |
| (-) SUPPLY             | (BLACK)   | -----o J201 | or | J201 <---   |

### MODIFICATIONS TONE UNIT

### RADIO

**USER:** Remove wires not used.

Pin designations for CTCSS connections seem to change with vintage. Late models are on the left early models on the right.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376  
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com