

Selectone

ST-139 APPLICATION NOTE #1410

FOR USE WITH: ICOM IC-02AT

APPROVAL DATE: 2MAR98S BY: RTS

CONNECTIONS
TONE UNIT RADIO

8	MONITOR	BLK/BRN		S104 N.O	
7	MONITOR	BROWN		GROUND	
10	P.T.T. (ENCODE ENABLE)	BLK/YEL		MTC2	PTT
6	P.T.T. (ENCODE ENABLE)	YELLOW		N/C	
5	DECODE (+)	BLK/ORG		N/C	
4	DECODE (-)	WHT/ORG		JUNCTION OF IC102-13 AND R182	
1	HI PASS FILTER OUTPUT	WHT/BLU		JUNCTION OF R132 AND C120	
11	HI PASS FILTER INPUT	BLUE		JUNCTION OF C120 AND R145	
2	HI PASS FILTER MUTE	VIOLET		N/C	
12	TONE INPUT	GREEN		JUNCTION OF R128 AND Q105	
13	ENCODE OUTPUT	WHT/GRN		JUNCTION OF R114 AND R115	
3	(+) SUPPLY	RED		JUNCTION OF Q106 AND R133	
9	(-) SUPPLY	BLACK		GROUND	

NOTES AND MODIFICATIONS

RADIO: REMOVE C120.

TONE UNIT: REMOVE JU1.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com