

Selectone

ST-139 APPLICATION NOTE #1419

FOR USE WITH: **Standard HX300 Series Portables** APPROVAL DATE: 08july98 BY:cpe

WDC	TONE UNIT	CONNECTIONS	RADIO
			J103 PINS
o---	MONITOR	BROWN	1
o---	MONITOR	BLK/BRN	7
o---	P.T.T. (ENCODE ENABLE)	BLK/YEL	2
o---	DECODE (+)	BLK/ORG	8
o---	HI PASS FILTER OUTPUT	WHT/BLU	9 (SEE NOTE 1)
o---	TONE INPUT	GREEN	6 (SEE NOTE 1)
o---	ENCODE OUTPUT	WHT/GRN	4
o---	(+) SUPPLY	RED	3
o---	(-) SUPPLY	BLACK	1

MODIFICATIONS	RADIO
USER:	1. REMOVE R168 (BETWEEN J103 PINS 6 AND 9)
FACTORY:	

Revised 07APR89 by WDC

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com