

Selectone

ST-200 APPLICATION NOTE #2130

FOR USE WITH: G. E. Mastr Executive II

APPROVAL DATE: 13JAN89 BY: WDC

CONNECTIONS

TONE UNIT

RADIO

(+) SUPPLY	(RED)		J907-2	10V REG
(-) SUPPLY	(BLACK)		J907-4	A-
TONE INPUT	(GREEN)		J907-8	VOL HI
MONITOR/HOOK SWITCH	(BROWN)		TB901-1 or J901-8 (as shown below)	
DECODE LATCHED	(WHT/ORG)		J907-9	CG DIS
DECODE MOMENTARY	(WHT/VIO)		USER SUPPLIED ALERT HORN	
LAMP (-)	(BLK/ORG)		USER SUPPLIED CALL LIGHT	
SET	(WHITE)		NOT USED	

MODIFICATIONS

TONE UNIT

RADIO

USER:		CG DIS -- > --*--o TB901-1 (BASE)
JU1=B		1N914 J901-8 (MOBILE)
JU3=OPEN		to
REPLACE Q4 WITH A 1N914 DIODE.		BROWN WIRE ---' MIC HANG-UP BOX
(CATHODE TO COLLECTOR CONNECTION		
AND ANODE TO BASE CONNECTION)		
FACTORY:		Break connection between CG DIS
		signal and TB901-1 or J901-8.
		Insert a diode in series as
		shown above. Connect the BROWN
		wire on the Mic hang-up side of
		the diode.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com