

Selectone

ST-200 APPLICATION NOTE #2134

FOR USE WITH: **Uniden SMU**

APPROVAL DATE: 17JUL89 BY: WDC

CONNECTIONS			
TONE UNIT			RADIO
(+) SUPPLY	(RED)	---	SWITCHED B+
(-) SUPPLY	(BLACK)	---	GROUND
TONE INPUT	(GREEN)	---	IC102-2
MONITOR/HOOK SWITCH	(BROWN)	---	HOOKSWITCH
DECODE LATCHED	(WHT/ORG)	---	BASE OF Q107
DECODE MOMENTARY	(WHT/VIO)	---	USER SUPPLIED HORN
LAMP (-)	(BLK/ORG)	---	USER SUPPLIED CALL LAMP
SET	(WHITE)	---	NOT USED

MODIFICATIONS			
TONE UNIT			RADIO
USER:			
REPLACE Q4 WITH A IN914 DIODE.			
CATHODE TO COLLECTOR, ANODE TO BASE.			
FACTORY:			

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com