

Selectone

ST-200 APPLICATION NOTE #2138

FOR USE WITH: Standard GX 3000

APPROVAL DATE: 25AUG89 BY: WDC

=====

CONNECTIONS

TONE UNIT

RADIO

(+) SUPPLY	(RED)		JR01-7
(-) SUPPLY	(BLACK)		JR04-3
TONE INPUT	(GREEN)		JR04-1
MONITOR/HOOK SWITCH	(BROWN)		JM01-1
DECODE LATCHED	(WHT/ORG)		BASE OF QA04
DECODE MOMENTARY	(WHT/VIO)		USER SUPPLIED HORN
LAMP (-)	(BLK/ORG)		USER SUPPLIED CALL LAMP
SET	(WHITE)		NOT USED

MODIFICATIONS

TONE UNIT

RADIO

USER:

REPLACE Q4 WITH A 1N914 DIODE,
CATHODE TO COLLECTOR, ANODE TO
BASE.

JU1=A

JU3=OPEN

FACTORY:

=====

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com