

Selectone

ST-809 APPLICATION NOTE #8188

FOR USE WITH : KENWOOD TK-840

APPROVAL DATE: 11NOV97R BY:RTS

CONNECTIONS

DECODER UNIT		RADIO	
(3)	(+) SUPPLY INPUT	RED	JUNCTION OF 8C AND R18
(9)	(-) SUPPLY INPUT	BLACK	GROUND
(11)	CALL LAMP #2	BLUE	GROUND
(1)	ALERT TONE	WHTBLU	IC9-7 (SEE NOTE BELOW)
(12)	DTMF SIGNAL INPUT	GREEN	IC9-1
(13)	TRANSPOND TONE	WHT/GRN	CN1-6 MI
(2)	CALL LAMP #1	VIOLET	BASE OF Q20
(10)	TRANSPOND PTT/SET	BLK/YEL	CN1-7 PTT
(7)	MONITOR/RESET	BROWN	J201-6 HOOK
(4)	DECODE LATCH	WHT/ORG	JUNCTION OF C92 AND Q19
(5)	DECODE MOMENTARY	BLK/ORG	HOOK TO HORN RELAY
(8)	NOT USED	BLK/BRN	NO CONNECTION
(6)	PTT INPUT	YELLOW	NO CONNECTION

NOTES: ADD A 0.1 CAPACITOR IN SERIES WITH THE WHT/BLU WIRE.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com