

Selectone

ST-809 APPLICATION NOTE #8193

FOR USE WITH : STANDARD GX4800UT

APPROVAL DATE: 16JAN98R BY:CPE

CONNECTIONS

DECODER UNIT		RADIO		
(3)	(+) SUPPLY INPUT	RED	JL01-19	SWED +B
(9)	(-) SUPPLY INPUT	BLACK	JL01-1	GROUND
(11)	CALL LAMP #2	BLUE	JL01-1	GROUND
(1)	ALERT TONE	WHT/BLU	QM01-21	
(12)	DTMF SIGNAL INPUT	GREEN	QM01-20	
(13)	TRANSPOND TONE	WHT/GRN	JL01-11	MIC
(6)	CALL LAMP #1	VIOLET	QA03-4	
(10)	TRANSPOND PTT/SET	BLK/YEL	JL01-10	PTT
(7)	MONITOR/RESET	BROWN	JL01-2	MIC HANG
(4)	DECODE LATCH	WHT/ORG	N/A	
(5)	DECODE MOMENTARY	BLK/ORG	N/A	
(8)	NOT USED	BLK/BRN	N/A	
(2)	PTT INPUT	YEL	N/A	

NOTES:

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com