

Selectone

ST-804

APPLICATION NOTE #8201

FOR USE WITH: MOTOROLA GP300/P110

APPROVAL DATE: 14JULY98S BY:CPE

CONNECTIONS
TONE UNIT

RADIO

3	(+) SUPPLY INPUT	RED	U404-8	SW B+
9	(-) SUPPLY INPUT	BLACK	P1-8	GND
12	ENI ACTIVATE	GREEN	USER ADDED SWITCH	
11	N/A	BLUE	N/C	
5	MIC MUTE	BLK/ORG	P1-5	TX AUDIO
6	P.T.T. SIGNAL INPUT	YELLOW	JUNCTION OF PB403 AND C468	
10	P.T.T. SIGNAL OUTPUT	BLK/YEL	JUNCTION OF Q408 AND R451	
1	N/A	WHT/BLU	N/C	
4	RS232 OUT	WHT/ORG	N/C	
13	ENCODE DTMF TONE OUTPUT	WHT/GRN	P1-4	OPTIONAL TX AUDIO
7	N/A	BRN	NOT USED IN RADIO APPLICATION	
2	RS232 IN	VIOLET	NOT USED IN RADIO APPLICATION	
8	N/A	BLK/BRN	NOT USED IN RADIO APPLICATION	

MODIFICATIONS
TONE UNIT

RADIO

USER:

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SmarTrunk Systems, Inc. • 23278 Bernhardt Street Hayward, CA. 94545 • Phone: (510) 887-1950
Fax: (510) 887-4011 • Website: www.selectone.com • E-Mail: technicalsupport@smartrunk.com