Selectone ST-809 APPLICATION NOTE #8206

FOR USE WITH: MOTOROLA SABER SPECIAL APPROVAL DATE: 25SEP98S BY:RTS

CONNECTIONS

	ANI UNIT		RADIO
(3)	(+) SUPPLY INPUT	RED	UNIVERSAL CONNECTOR PIN 8
(9)	(-) SUPPLY INPUT	BLACK	J6-2
(12)	RX SIGNAL INPUT	GREEN	UNIVERSAL CONNECTOR PIN 1 OR 2
(13)	TRANSPOND TONE	WHT/GRN	UNIVERSAL CONNECTOR PIN 4
(6)	PTT INPUT	YELLOW	NO CONNECTION
(10)	PTT OUTPUT	BLK/YEL	UNIVERSAL CONNECTOR PIN 9
(5)	DECODE MONENTARY	BLK/ORG	OUTPUT
(2)	CALL LAMP #1	VIOLET	OUTPUT
(4)	DECODE LATCH	WHT/ORG	OUTPUT
(8)	NO CONNECTION	BLK/BRN	NO CONNECTION
(7)	MONITOR	BROWN	UNIVERSAL CONNECTOR PIN 7 OR J6-2
(11)	CALL LAMP #2	BLUE	OUTPUT
(1)	ALERT TONE	WHTBLU	NO CONNECTION

NOTES: PROGRAM THE RADIO FOR OPT SEL TO GO TO GROUND TO ENABLE THE DECODER OR TIE THE BROWN WIRE TO GROUND.