

# Selectone

## ST-139 APPLICATION NOTE #9017

FOR USE WITH: KENWOOD TK-601S

APPROVAL DATE: 22SEP98 BY:CPE

=====

CONNECTIONS

TONE UNIT

RADIO

TONE UNIT		RADIO	
			J6
10	P.T.T. (ENCODE ENABLE) (BLK/YEL)	-<10	PTT
4	DECODE (-) (WHT/ORG)	-< 5	AC
1	HI PASS FILTER OUTPUT (WHT/BLU)	-< 6	AF O
12	TONE INPUT (GREEN)	-< 4	AF I
13	ENCODE OUTPUT (WHT/GRN)	-< 8	MOD
3	(+) SUPPLY (RED)	-< 7	SB
9	(-) SUPPLY (BLACK)	-< 1	GND
7	MONITOR (BROWN)		

2,5,6,8, & 11 are NOT used.

=====

MODIFICATIONS

TONE UNIT

RADIO

USER:

JU2-B POSITION

Remove jumper plug from J6;  
Cut JU2 on the PLL Board; Connect  
the tone unit to J6 with the  
BLACK wire at pin 1.

FACTORY: Splice the BROWN wire to  
the BLACK wire.

AP AS PER BELCO DIST

=====

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376  
(800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com