

# R-30M WILDLIFE TELEMETRY RECEIVER

## Features

- 144-174MHz Continuous frequency coverage, fully synthesized, in 100Hz steps
- 999 Memory channels with individual channel naming and a unique retune feature for adjusting memory channel frequencies
- Scanning of all 999 memory channels, 5 scan lists, and individual channel lockout
- Fully programmable with keypad, no computer required
- Backlit LCD display, programmable on and off, and backlit keypad
- .5ppm TCXO for superior temperature stability with no frequency drift
- Peak reading (0-99) sample and hold meter, with programmable hold time, responds to 5ms wide pulses
- Cloning of all memory channels between receivers with supplied cable, no computer required

## Specifications

- RF attenuator: -80dB of RF attenuation in 24 steps, plus -40dB of audio attenuation, for -120dB total
- Channel steps (programmable): 100Hz, 500Hz, 1kHz, 5kHz, 10kHz, or 100kHz
- Receiver mode: CW
- Antenna impedance: 50 ohms
- Antenna connector: BNC female and SMA male for supplied rubber duck
- Battery: 7.5v rechargeable Li-ion snap-on battery pack with spare supplied for extended operation
- Battery life: Approximately 12 hours for each battery pack
- Dimensions: 4.25" (108mm) x 2.30" (59mm) x 1.30" (33mm) excluding protrusions
- Mass: 8 ounces (225 grams)
- 1 Year Warranty

## Price (including all accessories)

**\$795.00**

Including free ground Continental USA shipping

## Accessories Supplied:

- 110vac Drop-in Fast Charger
- 12vdc Car Charger
- (2) Snap-on 1600ma Battery Packs
- Belt Clips
- Cloning Cable
- 6" Non-directional Rubber Duck Antenna for close-in use
- Antenna Adapters
- 5' Coax Cable
- and more



**COMMUNICATIONS SPECIALISTS, INC.**

1442 E. LINCOLN AVE., #349, ORANGE, CA 92865

E-MAIL: [sales@com-spec.com](mailto:sales@com-spec.com) • [www.com-spec.com](http://www.com-spec.com)

1-714-998-3021 EXT 101 or 1-800-854-0547 EXT 101

